



---

## **MicroSurvey FieldGenius 3.2 – Hot Fix**

### **Release Notes**

MicroSurvey FieldGenius 3.2 (v 3.2.10697)

16 January 2026

---

# Table of Contents

<b>New Features</b> .....	3
<b>Refinements</b> .....	4
<b>New/Updated Instrument Drivers</b> .....	4
GNSS.....	4
Total Station .....	4
<b>Defects Fixed</b> .....	5
<b>Known Issues</b> .....	6

# MicroSurvey FieldGenius 3.2 – Hot Fix

Introducing **FieldGenius 3.2**, a comprehensive and versatile **full survey solution** designed for both **Android** and **Windows** devices. This release enhances total station functionality, introduces numerous GNSS driver updates and new features, and delivers refinements and bug fixes for an improved user experience.

## New Features

### Total Stations Improvements

- Two new measure modes
  - Angle Offset
  - Distance Offset
- Four new stakeout modes
  - Stake Line Segment
  - Stake Line Defined by Points
  - TS Stake Station Offset (including alignment)
  - Stake Surface
- Target height is now recalled with target changes
- Continuous distance measurement available in reflector-less mode
  - for Leica and Geomax robotic instruments

### GNSS Enhancements

- Improved stake alignment mode
  - the elevations are calculated using vertical profiles or surfaces, with an option to select
- GNSS reference profile - base position can be sent via Internet
- Reset RTK Filters to force recalculation of new solutions and resolve ambiguities
- IMU calibration for Hemisphere and Stonex receivers

### New Functions

- Rotate, Translate, and Scale (RTS) functionality calculated from point pairs

- Horizontal point snapping in Manual Point mode
- New license type: Office License
  - For in-office project configuration. Cannot connect to any instruments.

## Refinements

- **Surface Staking** – user can stake a negative surface
- **Coordinate System page** - User can Expand/Collapse all filtered coordinate systems
- **Coordinate file Import** - Added functionality to include a prefix/suffix before import
- **3D mode** - Point size has been reduced
- **Export Raw file** - Added support for exporting to STAR\*NET with UTF8-BOM encoding for accurate conversion to .DAT in STAR\*NET
- **GNSS Offset Measure Mode Mobile Landscape** - Added map zoom controls
- **Windows File Manager** - Enabled 'Select' functionality via long-press gesture to match Android
- **Improved performance** navigating to New Project screen and Geodetic Calculator page (Android)

## New/Updated Instrument Drivers

### GNSS

- GeoMax Zenith55 & Zenith60Pro
- Leica FLX 100 Plus (requires Zeno Connect application)
- TokNav P8, P8Pro, P8 global driver
- Geoobchod, GeoGen
- GeoMeasure Pinpoint

### Total Station

- GeoMax Zoom10
- GeoMeasure GM-52

## Defects Fixed

- **3.2 Hot Fix change:** Fixed an application crash triggered by points and line data panel update events.
- **3.2 Hot Fix change:** Corrected application not responding state management during deletion of lines and points with associated stakeout results
- Implemented fixes to prevent database corruption
- Corrected the base position transmission error that occurred during the day 2 setup when local transformation was applied
- Fixed missing date selector in Filter Points' Date Range (Windows)
- Leica/Geomax total station drivers: Added 'low battery' warning
- Fixed crash related to the calculation algorithm for TS Setup map drawing line
- Fixed crash when exporting LandXML files with Total Station Observations
- ComNav N3: Fixed the missing APN
- Fixed issue where upgrading from 3.1 to 3.2 or 3.0 to 3.2 will not delete the instrument profiles (Windows only)
- Fixed issue where Geomax Zoom35 Pro couldn't select the Mountpoint on Windows
- Fixed issue on Tripletek 9 Pro tablet in landscape mode where UI elements were cut off in staking robotic total station dialogs
- Implemented fixes to prevent of database corruption
- Fixed issue where DXF import deleted project codes
- Fixed issue where Target Height was not applied in Check Measurement mode
- Fixed issue with incorrect logging of timestamp data in Check Measurement mode
- Stonex S980+: Fixed issue with inability to observe with Reference after the first setup on Stonex
- Observation panel: Resolved flickering issue in the observation panel [Windows only]
- DWG/DXF export: Incorrect warning message during DWG/DXF export was removed
- Raw File - Fixed issues with raw file sequence when using the overwrite option
- Emlid RS3: Fixed an issue with the GNSS Survey Report where the baseline distance value was incorrectly displayed as 0
- Resolved an issue in the Czech Republic S-JTSK (v1710) (Quadrant 1) where COGO and staking displayed incorrect values when a background map was not used.

## Known Issues

- **New 3.2 know issue:** The reference position is not set correctly during the base setup process when the user attempts to use the averaged observed point.
- **Raw file issue** with Star\*NET import: Raw file export written differently than FieldGenius Legacy in one specific case when storing Totals station Backsight direction and point simultaneously (Workaround: Observe Angle only then take side shot separately)
- **Rotate/Translate/Scale**
  - When observed points are transformed, the Observation Detail page and GNSS report display the observed Cartesian coordinates, while the point list displays the transformed coordinates.
  - Points containing GIS features cannot be translated, rotated, or scaled
- **CHC drivers** available only on the Android platform
- **Auto-recording** - delay in storing points when collected in 1sec paste
- **Import DXF/DWG** – various issues while importing CAD drawings
- **Leica GS16** - unable to receive RTK corrections from NTRIP on Windows devices
- **HeXML Export** – missing baseline information and incorrect point role assignments
- **Leica GS16** - Issue with some specific source tables
- **Septentrio NR3** - Issue with receiving corrections
- **Spectra Precision 60** – Issue with configuring UHF radio
- **Temporary Antenna Height** – Issue with height computation when IMU tilt correction is enabled
- **3D View** - Is only available on Android. Windows users can only view in a 2D top-down view
- On some Android devices, FieldGenius does not automatically launch after installation. However, it is installed; the Application must be started manually
- **Czech S-JTSK Issue:** Coordinate conversion error when adding from external reference between Quadrant 1 and Quadrant 3, and vice versa.